



TECHNICAL SHEET

Pumping station NEBBIASECCA® ECOPACK III

MAIN APPLICATIONS:

- Textile Industries
- Graphics and printing.
- Woodworking.
- Automotive.
- Electronics Industry.

ADVANTAGES:

- Small size.
- Compact and resistant structure.
- Suitable for continuous operation.

ACCESSORIES INCLUDED:

- Glycerine pressure gauge.
- Adjustable pressure switch.
- Calibrated safety valve.
- Electrical panel

OPTIONALS:

- Bactericidal UV lamp
- Remote control



Technical Characteristics

Parameter	Specify
Pump type	With ceramic pistons
Scope	Fm 1 to 14 litri/min
Operating pressure	70 bar
Materials	Brass pump head
Motor	Triphase 400V – 50Hz
Assembly	Panelled aluminium structure and glycerine pressure gauge
Dimension	mm. 650x440x650
Dry weight	35 Kg
Filtration unit	10" composed of 5 micron cartridge

The ECOPACK III pump unit is the ideal solution for all industrial applications that require high-pressure water in a continuous, efficient and controlled manner. Designed to guarantee high performance and reliability, it integrates a ceramic piston pump with an intelligent inverter in an external panel, which allows the pressure to be automatically adjusted based on the actual demand of the system, optimising consumption and performance.

Thanks to its compact structure, the ECOPACK III unit is also suitable for the most demanding environments such as those in the textile, graphics, woodworking, winemaking, electronics and many other sectors.

ECOPACK III is the perfect choice for those looking for a compact solution, long-term reliability and maximum process control.

MENDIZZA S.R.L. - Via Gramsci, 232 - 13876 Sandigliano BI – ITALY
Tel. +39- 015 - 541233

Reg. Imprese Cod. Fisc. e p. I.V.A. IT01499900023

www.mendizza.com info@mendizza.com

R.E.A.CCIAA BI 142737 Cap. Soc. € 80.000 i.v.